



NATA LIGHTING CO.,LTD.
www.nata.cn
Email:info@nata.com
Tel:+86-750-3770000 Fax:+86-750-3771111
Address:380JinOu Road,GaoXin Zone,Jiang Men City,Guangdong,China

Nata

LumCAT: LN01D03515DA-N

Luminaire: 92.70.267.00

Report No: 200923-B005

Test No: 200923-C005

LampCAT: CLU700 LES6

Lamp flux(lm): 626.5

Number of Lamps: 1

Length(mm): 0

Phm Type: C

Voltage(V): 29.5000

Current(A): 0.1900

Power (W): 5.6050

PF: 0.0000

Ballast type: DC

Width(mm): 0

Height(mm): 0

Photometric Results

Lumens(lm): 545.91

Efficiency(%): 87.14%

Lumens(lm)/Power(W): 97.40

Central intensity(cd): 3956.766

Maximum intensity(cd): 3956.766

Angle of maximum intensity: C=0.0 γ =0.0

Beam Angle(50%Imax): [C0/180]Total=18.1

[C90/270]Total=18.1

Field angle(10%Imax): [C0/180]Total=33.7

[C90/270]Total=33.7

Maximum s/h(1/2): C0_180=0.31 C90_270=0.31

Maximum s/h(1/4): C0_180=0.31 C90_270=0.31

Up flux rate of lamp(%): 0.00%



Down flux rate of lamp(%): 87.14%

Up flux rate of LUM(%): - -

Down flux rate of LUM(%): 100.00%

CIE Type : Direct lighting

Output flux ratio in π solid angle : 96.271%



C0(Max): ———

C0/C180: ———

C90/C270: ———

Field angle(10%Imax):C0/180Left:16.9 Right:16.9
:C90/270Left:16.9 Right:16.9

Beam Angle(50%Imax):C0/180Left:9.1 Right:9.1
:C90/270Left:9.1 Right:9.1